

Leica Zeno GG03

Upgradeable GNSS/GIS SmartAntenna Datasheet



Upgradeable, reliable and accurate GNSS technology

The Leica Zeno GG03 is completely upgradeable; starting as an L1 only DGPS SmartAntenna up to a highly accurate L1/L2 GNSS SmartAntenna. Built on years of knowledge and experience, the GG03 combines a high-performance GNSS SmartAntenna with complete reliability.

- The GLONASS option improves satellites tracking in obstructed locations
- The L2 option delivers cm accuracy in RTK or post-processed
- High-accuracy, jamming resistant measurement engine, to ensure accurate and reliable results in the most demanding environments for all in-view satellite tracking

Built for the field

Designed for extreme environments – rugged, light-weight, and cable-free.

- With IP68 the GG03 is built to withstand the most toughest field whilst maintaining an ergonomic, light-weight and compact design
- Built to operate in extreme temperatures -40 °C to +65 °C
- Easily exchangeable all-day-battery

Designed for versatile use

Choose the field computer, the field software and the setup (pole or backpack) to suit your workflow and budget.

- Ready-to-use with Leica Zeno Field and Leica MobileMatrix
- Various Leica Geosystems handhelds and tablet computers supported, such as Leica Zeno 5, Zeno 10 & Zeno 15, and the Leica CS25
- Use Leica Zeno Connect to embed custom applications

Technical Specifications

Leica Zeno GG03

GNSS Technology

Channels	120 channels L1 only, Optional: L1/L2 GPS, Optional: Glonass
Satellite signals tracking	GPS: L1, L2, L2C (C/A, P, C Code) GLONASS: L1, L2 (C/A, P narrow Code) BeiDou: B1 Galileo: E1
Real-Time and Post-processed	Support of real-time correction service and post-processing to achieve positioning accuracy
Output data protocols	NMEA-0183 (GGA, VTG, GLL, GSA, ZDA, GSV, RMC, GST, GRS) via Zeno Connect
Update rate	1 Hz (1 sec), Optional: 5Hz (0.2 sec)
Post Processing accuracy static mode	Horizontal: 3 mm + 0.5 ppm (rms) ¹ Vertical: 6 mm + 0.5 ppm (rms) ¹
Horizontal real-time accuracy (SBAS or external source)	SBAS (L1 only): < 0.9 m ¹ DGNSS (L1 only): < 40 cm ¹ RTK (L1/L2): 1 cm + 1 ppm ¹
Vertical real-time accuracy	RTK (L1/L2): 2 cm + 1 ppm ¹
Real-time protocols	RTCM 2.x, RTCM 3.0, RTCM 3.1, Leica, CMR, CMR+
Integrated real-time	SBAS (WAAS, EGNOS, MSAS) ³
Time for initialisation	Typically 6 sec ²

GG03 SmartAntenna

User interface	On/Off key Status indicator (LED): satellite tracking, Bluetooth® communication & battery power
Communication port	Bluetooth® 2.0 class 2 & sealed and protected 8-pin Lemo combined USB / power port
Field controller connection	By Bluetooth® or with GEV162 RS232 cable

Power Management

Removable battery	GEB212 (7.4 V / 2600 mAh Li-Ion rechargeable)
Battery charging time	2 hours to full charge with GKL211
Power	Nominal 12 V DC Range 10.5 – 28 V DC
Operating time	10 h (GNSS only) ⁶ , 8 h (RTK) ⁶

Physical Specifications

Weight	0.8 kg with all-day battery 2.6 kg ready-to-use with Leica CS10 3.5G GIS, pole and batteries 2.3 kg ready-to-use with Leica Zeno 5, pole and batteries
Environmental specifications	IP68: dust and water-resistant for all conditions Temporary submersion into water (max. depth: 1 m) Protected against blowing rain and dust
Operating / storage temperature range ⁴	Operation: -40 to 65 °C (-40°F to +149°F) Storage: -40 to 80 °C (-40°F to +176°F)
Humidity	100%, non-condensing ⁵
Drop	Withstands topple over from a 2 m survey pole onto hard surface Withstands 1 m drop onto hard surface
Vibration	Withstands vibration in compliance with ISO9022-26-08

Accessories and Optional Features

Accessories	<ul style="list-style-type: none"> External battery charger Backpack kit Hard carry case 2 meter range pole
Optional Field and Office software	<ul style="list-style-type: none"> Leica Zeno Field Leica MobileMatrix Leica Zeno Connect Leica Zeno Office and Leica Zeno Office on ArcGIS
Optional field computers	<ul style="list-style-type: none"> Leica Zeno 5 Leica CS25 rugged Tablet Computer Leica Zeno 10 and Zeno 15 GNSS/GIS handhelds Leica CS10 GIS and CS15 GIS field controllers

¹ Measurement precision, accuracy and reliability depends upon various factors including number of available satellites, geometry proximity to base station, multipath effects, ionospheric conditions etc.

² May vary due to atmospheric conditions, multipath, obstructions, signal geometry and number of tracked satellites.

³ WAAS available in North America only, EGNOS available in Europe only, and MSAS available in Japan only

⁴ Compliance with ISO9022-10-8, ISO9022-11-special and MIL-STD-810F Method 502.4-II, MIL-STD-810F method 501.4-II

⁵ Compliance with ISO9022-13-6, ISO9022-12-04 and MIL-STD-810F Method 507.4-I

⁶ May vary with temperature, battery age, usage etc.



The Bluetooth® word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under license.

Other trademark and trade names are those of their respective owners.

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2012. 804731en - 10.14 - galledia